

Heavy-Duty Taper Bolts

by MKT Fastening

Features/Advantages

- Grade 5, zinc plated
- Required hole diameter equals anchor diameter
- Variation in hole size can be accommodated by turning the expander nut
- Equipment may be removed and replaced. The bolt is simply re-inserted and torqued to obtain original holding power (the nut stays in the hole)
- Bolt can be removed and re-used with a new nut after cleaning and lubricating the threads
- Strength – the highest shear strength of any expansion anchor
- Withstands vibratory loads
- Works in a bottomless hole
- Do not use in brick or block
- Tested by Pittsburgh Testing Laboratory PG-2170
- **Made in the USA**



Cat No.	Description	Box Qty.	Box Wt. (lbs.)	Master Qty.	Master Wt. (lbs.)
Taper Bolts					
3420000-	3/8" X 2-1/4" Taper Bolt	50	4.4	400	35
3421000-	3/8" X 2-5/8" Taper Bolt	50	5	400	40
3422000-	3/8" X 3" Taper Bolt	50	5.6	400	45
3423000-	3/8" X 4" Taper Bolt	50	7.1	400	57
3430000-	1/2" X 2-7/8" Taper Bolt	25	5	200	40
3431000-	1/2" X 4" Taper Bolt	25	6.5	200	52
3432000-	1/2" X 5" Taper Bolt	20	6.4	100	32
3440000-	5/8" X 3-1/2" Taper Bolt	20	7.6	100	38
3441000-	5/8" X 4-1/2" Taper Bolt	25	12	75	36
3442000-	5/8" X 6" Taper Bolt	25	15.3	75	46
3443000-	5/8" X 7" Taper Bolt	25	17	75	51
3450000-	3/4" X 4-1/8" Taper Bolt	20	13	60	39
3451000-	3/4" X 5-1/2" Taper Bolt	20	16.3	60	49
3452000-	3/4" X 7" Taper Bolt	15	15	45	45
3453000-	3/4" X 8" Taper Bolt	15	17.3	45	52
3460000-	1" X 5-5/8" Taper Bolt	10	15.3	30	46
3462000-	1" X 7-1/4" Taper Bolt	10	19.5	20	39
Taper Bolt Nuts					
3420200-	3/8" Taper Bolt Nut	100	0.8	3,000	25
3430200-	1/2" Taper Bolt Nut	50	1.4	600	17
3440200-	5/8" Taper Bolt Nut	50	2.3	600	27
3450200-	3/4" Taper Bolt Nut	50	3.1	400	25
3460200-	1" Taper Bolt Nut	10	1.5	120	18



Contact us today for a quote!

Hurripanel™ Fasteners

2128 Springwood • Carrollton, TX 75006

1.972.417.8882

www.hurripanel.com