

Holly Hollow Wall Anchors

by MKT Fastening

Features/Advantages

- Multi-legged sheet metal shell with machine screw, zinc plated
- Light to medium loads under dead or variable conditions in a variety of hollow base materials
- Expanded, the shell is permanently installed and fixtures can be exchanged by removing and replacing the screw
- Drive Holly does not require a pre-drilled hole

Concerns

- Hollow construction only

Approvals/Listings

- Regular: G.S.A. Spec FF-B-588D, Type III, Class A
- Drive: G.S.A. Spec FF-B-588D, Type III, Class B



Cat No.	Description	Grip	Box Qty.	Box Wt. (lbs.)	Master Qty.	Master Wt. (lbs.)
Regular Holly Hollow Wall Anchors						
120000-	1/8" XS	0 to 3/16"	100	0.9	3,000	28
121000-	1/8" SR	1/8" to 5/8"	100	1.4	1,200	17
122000-	1/8" LR	5/8" to 1-1/4"	100	1.9	800	15
123000-	1/8" XLR	1-1/4" to 1-3/4"	100	2.4	800	19
130000-	3/16" SR	1/8" to 5/8"	100	3.6	500	18
131000-	3/16" LR	5/8" to 1-1/4"	100	4.4	500	22
132000-	3/16" XLR	1-1/4" to 1-3/4"	100	5.3	300	16
140000-	1/4" SR	1/8" to 5/8"	100	5.0	500	25
141000-	1/4" LR	5/8" to 1-1/4"	50	3.1	400	25
142000-	1/4" XLR	1-1/4" to 1-3/4"	50	3.6	400	29
Drive Holly Hollow Wall Anchors						
150000-	1/8" XSD	1/16" to 1/4"	100	1.2	1,200	14
151000-	1/8" SD	1/2" to 1/2"	100	1.4	1,200	17
152000-	1/8" SLD	1/8" to 3/4"	100	1.8	1,200	21
Setting Tool						
110000-	Setting Tool	-	1	1	1	1

Contact us today for a quote!

Hurripanel Fasteners



**HURRIPANEL™
FASTENERS**

1.972.417.8882
or toll-free **1. 877.424.7616**
www.hurripanel.com