

Sup-R-Drop® Mechanical Anchors

by MKT Fastening

Features/Advantages

- Ideal for flush-mounting applications
- Preassembled for ease of installation
- Female threads accept standard UNC bolts or threaded rods (1/4" to 3/4")
- Slotted body is precision-matched to tapered internal plug for uniform expansion
- Knurled body increases frictional forces between anchor and wall of hole

Concerns

- Dead load only
- Hole depth must be equal to anchor length
- Do not overtorque



Approvals/Listings

- G.S.A. Spec FF-S-325C, Group VIII, Type 1
- UL-listed 3/8"-3/4"
- FM approved 3/8" - 1/2" & 3/4"

Cat No.	Description	Box Qty.	Box Wt. (lbs.)	Master Qty.	Master Wt. (lbs.)
Carbon Steel Sup-R-Drop Anchors					
1314000-	1/4"	100	2.5	1,000	23
1338000-	3/8"	50	3.3	500	31
133800L-	3/8" Lipped Sup-R-Drop	50	3.3	400	26
13380SH-	3/8" Super-R-Shorty Anchor	100	3.3	800	26
1312000-	1/2"	50	6.1	250	30
1358000-	5/8"	25	8.2	125	40
1334000-	3/4"	25	5	50	25
304 Stainless Steel Sup-R-Drop Anchors					
1314SS0-	1/4" 304 Stainless Drop-in	100	2.5	1,000	23
1338SS0-	3/8" 304 Stainless Drop-in	50	3.4	500	31
1312SS0-	1/2" 304 Stainless Drop-in	50	6.1	250	30
1358SS0-	5/8" 304 Stainless Drop-in	25	8.2	125	40
1334SS0-	3/4" 304 Stainless Drop-in	25	5	75	25
316 Stainless Steel Sup-R-Drop Anchors					
1314SS6-	1/4" 316 Stainless Drop-in	25	0.6	300	19
1338SS6-	3/8" 316 Stainless Drop-in	25	1.8	300	21
1312SS6-	1/2" 316 Stainless Drop-in	25	3.3	300	26
1358SS6-	5/8" 316 Stainless Drop-in	25	6.6	125	33
1334SS6-	3/4" 316 Stainless Drop-in	25	12.7	75	38
Coil Thread Sup-R-Drop Anchors					
1312CT0-	1/2" Coil Threaded Drop-in	50	6.1	250	30
1334CT0-	3/4" Coil Threaded Drop-in	25	5	50	25
Sup-R-Drop Setting Tools					
1314700-	1/4" Setting Tool	1	0.2	1	0.2
1338700-	3/8" Setting Tool	1	0.2	1	0.2
1312700-	1/2" Setting Tool	1	0.3	1	0.3
1358700-	5/8" Setting Tool	1	0.3	1	0.3



Contact us today for a quote!

Hurripanel™ Fasteners

2128 Springwood • Carrollton, TX 75006

1.972.417.8882

www.hurripanel.com