

Sup-R-Lead®



Available Materials

- Lead alloy, die cast

Features/Advantages

- Light to medium loads in a variety of solid masonry
- Highly corrosion resistant

Approvals/Listings

- G.S.A. Spec FF-S-325C, Group IV, Type 1

Concerns

- Dead loads only

Order Detail

Order Code	Size	Hole Dia.	Ultimate Loads in Lbs.*		
			Tension	Box Quantity	Master Quantity
3531	6-8 x 3/4	1/4"	183	100	3,000
3532	6-8 x 1	1/4"	183	100	3,000
3533	6-8 x 1 1/2	1/4"	183	50	1,500
3535	10-14 x 3/4	5/16"	310	100	3,000
3536	10-14 x 1	5/16"	310	100	1,200
3537	10-14 x 1 1/2	5/16"	310	100	1,200
3541	16-18 x 1	3/8"	415	100	1,200
3542	16-18 x 1 1/2	3/8"	415	100	800

* Tested in 3000 P.S.I. Concrete.

Installation

- 1 Drill recommended diameter hole to depth of shield.
Clean hole of debris.
- 2 Insert lead anchor into hole.
- 3 Place fixture over anchor, insert screw and tighten.
Screw length must be length of anchor plus thickness of material to be fastened.

