

Zap-It®



Available Materials



- Zinc Zap-It body with:
- Carbon steel nail, zinc plated
- Stainless steel nail

Features/Advantages

- Required hole diameter equals anchor diameter
- Fast, easy installation
- Stainless steel nail and zinc anchor body allow for fastening in

Installation

- 1 Drill hole to length of product selected.
Clean hole of debris.
- 2 Insert "Zap-It" through material, place in hole and tap nail until flush with head.



Concerns

- Dead loads only
- Not recommended for eccentric loading

Approvals/Listings

- G.S.A. Spec FF-S-325C, Group V, Type 2, Class 3

Order Detail

Order Code	Stainless Steel	Anchor Diameter & Length	Hole Diameter	Embedment	Ultimate Loads in Lbs. 3000 P.S.I.			Box Quantity
					Tension	Shear		
3912	—	3/16 x 7/8	3/16"	5/8"	—	—	100	
3916	3916SSO	1/4 x 1	1/4"	3/4"	750	1516	100	
3920	3920SSO	1/4 x 1 1/4	1/4"	1"	1000	1516	100	
3924	—	1/4 x 1 1/2	1/4"	1 1/4"	1100	1516	100	
3928	—	1/4 x 2	1/4"	1 3/4"	1400	1516	100	
3930	—	1/4 x 3	1/4"	1 3/4"	1400	1516	100	

Contact Hurripanel Fasteners for a Quote
1.972.417.8882 • www.hurripanel.com